



k82



k82

The frezza by Transwall k82 system affords high acoustical performance in a sleek, low profile design. Offering great flexibility and style with multiple door, hardware, and finish options.

The k82 can accommodate both single and double glaze, allowing for a seamless transition across the floor while maintaining the same profile and aesthetic. With the ability to accommodate glass and solid panels, the possibilities are limitless.



k82 Product Specifications

Frame Dimensions:	3 ¼" W x 1 9/16" H
Panel Options:	Double-Glazed, Single Offset-Glazed, Solid
Maximum Glass Size:	10'H, 42"W (other sizes available, project specific)
Leveling Tolerance:	+/- 5/16" Leveling in the ceiling only
Ceiling Connection:	Soffit Installation
Glazing:	½" Tempered and Laminated, ½" Low Iron, ½" Acid-Etched Glass, 3/8" Tempered and Laminated, Clear Polycarbonate Glazing Channel, MDF Substrate
Door Options:	Single-Glazed Frameless Sliding & Pivot, Single-Glazed Framed Sliding & Pivot, Double-Glazed Framed Sliding & Pivot, Veneer/Painted Sliding & Pivot, Pocket
Hardware:	Locking and Non-locking Ladder Pulls, Cylindrical & Mortise Locksets, Offset Pivot Hinges, Roller Hardware
Finishes:	Polished & Anodized Aluminum, Fabric Wrapped, Melamine, Markerboard, Veneer, Powder Coat Paint (custom color available)
STC:	46
Lead Time:	6 weeks after receipt of approved shop drawings & field measurements
Manufacturing Location:	Treviso, Italy (500 L.F. kept in stock in West Chester, PA)