

## PRODUCT SCOPE

### GENERAL NOTES

- » Adjustability: +/- 1/2" Tolerance (see supplemental sheets)
- » Finishes: Powder Coat
- » Floor Attachment: Physical anchoring required
- » Ceiling Attachment: Ceiling grid or Soffit attachment

### PANEL GLASS

- » Widths up to 42"
- » Heights up to 10'-0"
- » Types
  - » 1/2" Clear Tempered
  - » 1/2" Clear Tempered Low Iron

### CONNECTOR CONDITIONS

- » 8"w Aluminum Bypass Panel (default), 4"w & 6"w (available)
- » 2" Bypass Back-to-Back Verticals
- » Finished End
- » Wall Start at Door Frame
- » Wall Start at Panel

### TRIM

- » 2-Way with Bulb Seal (Lap Joint)
- » 2-Way 90° Corner Vertical Accent
- » 3-Way with Bulb Seal (2 pieces of glass)
- » 3-Way Vertical Accent (requires 3 pieces of glass)
- » 4-Way with Bulb Seals (3 pieces of glass)
- » 4-Way Vertical Accent (requires 4 pieces of glass)

### SLIDING DOOR FRAMES | DOORS | HARDWARE

- » Single Full Height Sliding Frame
- » Double Full Height Sliding Frame
- » Frameless Glass Door
  - » 1/2" Clear Tempered
  - » 1/2" Clear Tempered Low Iron
- » 1x2 Thin Aluminum Glass Framed Door
  - » 3/8" Clear Tempered Glass
  - » 3/8" Glass Tempered Low Iron Glass
  - » 3/8" Laminated Tempered Glass
- » Non-Locking Ladder Pull
- » Deadbolt Down Locking Ladder Pull
- » Deadbolt Up Locking Ladder Pull
- » Soft Open/Close (optional)

### PIVOT DOOR FRAMES | DOORS | HARDWARE

- » Single Full Height Pivot Frame
- » Double Full Height Pivot Frame
- » Single Transom Height Pivot Frame
- » Double Transom Height Pivot Frame
- » Frameless Glass Pivot Door (up to 9'-0")
  - » 1/2" Clear Tempered
  - » 1/2" Clear Tempered Low Iron
- » 1 3/4" Door
  - » Flush Wood Pivot Door (up to 10'-0")
  - » Full Glass Wood Pivot Door (up to 10'-0")
  - » Full Glass Aluminum Pivot Door (up to 10'-0")
- » FSB Pivot Latchset & Lockset
- » PBA Pivot Latchset & Lockset
- » Modern Floor Door Stop
- » Floor Mounted Closer
- » Overhead Concealed Closer (1-3/4" thick doors only)
- » Electromagnetic Lock
- » Surface Mounted Door Bottom
- » Semi-Mortised Door Bottom (Wood door only)



**GLASS**

# Statement of Line

## PANELS

- » Edges will be Ground
- » ½" TEMPERED GLASS (Plate)

## DOORS | SLIDING

- » Edges will be Polished
- » ½" TEMPERED GLASS (Plate)

## DOORS | PIVOT

- » Edges will be Polished
- » ½" TEMPERED GLASS (Plate)

**TOLERANCE**

- » Panels have a tolerance of  $\pm 1/2"$ 
  - » Ex. Panel made to fit a ceiling height of 108". This panel will work if ceiling height is 107-1/2" – 108-1/2"
- » Sliding doors can be adjusted up and down 1/8". They will work with the same  $\pm 1/4"$  tolerance as panels, however any additional variance beyond the 1/8" adjustment will increase or decrease the nominal 5/8" undercut
- » Pivot doors are the least forgiving. At nominal, there is a 5/8" undercut and 1/8" reveal above the door. Any variation from nominal will directly affect the undercut and reveal.
- » GC holding a ceiling height to  $\pm 1/4"$ . Worst case scenario is if the actual ceiling height is 1/4" lower than nominal and a pivot door is made slightly large, it may not fit.

GLASS HEIGHT = Ceiling Height -  $4\frac{1}{8}"$

