

Zone

General

- System Thickness: 3-1 1/16"
- Unitized frames
- No shelf standard slots; storage units hung via mid-rails
- Panel Max Width: 48" (frame spanning avail. for solid tiles; textiles would be railroaded if required)
- Panel Min. Width: 8" solid; 12" clerestory; 36" beltline electric
- Panel Width Increments: 1"
- Panel Max Height: 10'
- Clerestory Min. Height: 12"
- Panel Height Increments: 1"
- Adjustability: +/-1" at base
- Floor Attachment: floor track fastened to floor
- Ceiling Attachment: soffit or ceiling grid

Conditions

- Straight Runs
- Finished Ends
- Foreign Wall Attachments
- 2-way
- 3-way (no direct connection required; universal post available)
- 4-way
- Building & Furniture Module

Reveal

- 1-1/2" ceiling
- 1-1/4" floor (nominal)
- 1/8" panel to panel (less fabric thickness)

Compliance Wall

- Base unit (mid-height) w/internal structural support post
- Window unit stacked on top of base unit
- Top & vertical end caps
- Base max height: 48"

Electrical

- Available in panel face only; base N/A
- Hard Wired
- Quick Disconnect

Doors

- Butt-hinge wood (flush & glass)
- Butt-hinge aluminum glass (Hutt's)
- Hydraulic-hinge 1/2" frameless glass

Tile Finish

- Powder coated steel including Markerboard option
- Fabric wrapped (max width determined by fabric selection)
- Vinyl wrapped (COM or CS)
- Wood (FSC available)
- Double glazed clerestory:
 - 1/4" tempered monolithic
 - 1/4" tempered laminated
 - 1/4" annealed laminated

Panel Type

- Full Solid
- Segmented Solid/Glass

Performance Tests

- ASTM E 90 – Sound Transmission Class (STC)
- ASTM E 84 – Flame Spread
- ANSI/BIFMA X5.6 – Load

